

AD *A129089*

MEMORANDUM REPORT ARBRL-MR-03271

**ROOTS: THE SEARCH FOR ZEROS OF THE
CHARACTERISTIC FUNCTION FOR THE SOLID ROD**

James N. Walbert

May 1983



**US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND
BALLISTIC RESEARCH LABORATORY
ABERDEEN PROVING GROUND, MARYLAND**

Approved for public release; distribution unlimited.

Destroy this report when it is no longer needed.
Do not return it to the originator.

Additional copies of this report may be obtained
from the National Technical Information Service,
U. S. Department of Commerce, Springfield, Virginia
22161.

The findings in this report are not to be construed as
an official Department of the Army position, unless
so designated by other authorized documents.

*The use of trade names or manufacturers' names in this report
does not constitute endorsement of any commercial product.*

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. REPORT NUMBER MEMORANDUM REPORT ARBRL-MR-03271	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) ROOTS: THE SEARCH FOR ZEROS OF THE CHARACTERISTIC FUNCTION FOR THE SOLID ROD		5. TYPE OF REPORT & PERIOD COVERED
		6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) JAMES N. WALBERT		8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS U.S. Army Ballistic Research Laboratory ATTN: DRDAR-BLI Aberdeen Proving Ground, MD 21005		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS 11162618AH80 AD
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Armament Research & Development Command US Army Ballistic Research Laboratory (DRDAR-BLA-S) Aberdeen Proving Ground, MD 21005		12. REPORT DATE May 1983
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		13. NUMBER OF PAGES 19
		15. SECURITY CLASS. (of this report) UNCLASSIFIED 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited		
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Characteristic equation Newton's method Method of bisection		
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) jmk The method of calculation of roots of the characteristic equation for the solid rod is presented. Difficulties with Newton's method are shown to be circumvented by application of a modified method of bisections.		

TABLE OF CONTENTS

	PAGE
LIST OF ILLUSTRATIONS.....	5
I. INTRODUCTION.....	7
II. THE CHARACTERISTIC FUNCTION FOR THE SOLID ROD.....	7
III. THE FAILURE OF NEWTON'S METHOD.....	8
IV. THE MODIFIED METHOD OF BISECTION.....	9
V. CONCLUSIONS.....	10
REFERENCES.....	14
DISTRIBUTION LIST.....	15

LIST OF ILLUSTRATIONS

Figure	PAGE
1. The Real and Imaginary Parts of $\Delta(z)$ in the xy -Plane.....	11
2. The Real Part of $\Delta(z)$ in the 1st and 5th Quadrants.....	12
3. The Imaginary Part of $\Delta(z)$ in the 1st and 5th Quadrants.....	13

I. INTRODUCTION

In the analysis of stresses in gun tubes, particular difficulties are encountered near surface boundaries such as at the muzzle, or near discontinuities in stress loading such as at the rotating band of the projectile. The analytic description of stress behavior in such regions is in the class of problems termed end stresses in semi-infinite cylinders. Currently, the Ballistic Research Laboratory (BRL) is supporting work in this area through contract* with Dr. David A. Spence of Oxford University and the Imperial College, U.K.

The research discussed in this report was conducted in support of Dr. Spence's work. Specifically, in view of the existence of BRL'S Bessel function subroutine¹ and experience in computing characteristic roots for the hollow cylinder, Dr. Spence requested the BRL to provide him with a tabulation of the first 1000 roots of the characteristic equation for a range of values of Poisson's ratio.

II. THE CHARACTERISTIC FUNCTION FOR THE SOLID ROD

Cauchy's method of characteristics was applied by V.K. Prokopov² to obtain the characteristic equation for a hollow cylinder with stress-free surface. A similar process for the geometry of the semi-infinite solid rod with a stress-free surface leads to the characteristic equation

*European Research Office, U.S. Army, Contract No. DAJA 37-80-C-0192.

¹K.L. Zimmerman, A.S. Elder, A.K. Depue, "User's Manual for the BRL Subroutine to Calculate Bessel Functions of Integral Order and Complex Argument," Technical Report ARBRL-TR-02068, Ballistic Research Laboratory, 1978 (AD A056369).

²V.K. Prokopov, "Equilibrium of an Elastic Axisymmetrically Loaded Thick-Walled Cylinder," *Prikadnaya matematika i mehanika*, Vol XIII, 1949, pages 135-144. Institute of Mechanics of the Academy of Sciences, USSR, FTIO Translation No. J-2589, Aberdeen Proving Ground, Maryland, Translation dated 22 August 1967.

$$\Delta(z) = 0 \quad (1)$$

where

$$z\Delta(z) = \begin{vmatrix} I_0(z) & [z^2 + (2-2\nu)] I_1(z) \\ I_1(z) & z^2 [I_0(z)] \end{vmatrix}, \quad (2)$$

I_0 and I_1 are modified Bessel functions of the first kind, of order 0 and 1, respectively, and ν is Poisson's ratio.

The roots of Eq. (1) correspond to the poles of the integrands in the Fourier integrals representing the stresses. The values of z satisfying Eq. (1) are therefore needed for calculations based on residue theory. It should be noted that if Z_0 is one such root, then \bar{Z}_0 , $-Z_0$, and $-\bar{Z}_0$ are also roots, where \bar{Z}_0 denotes the complex conjugate of Z_0 . Thus, only roots in the first quadrant need be considered.

To evaluate $z \Delta(z)$, use was made of the BRL Bessel function subroutine¹ in the equation

$$z\Delta(z) = z^2 [I_0(z)]^2 - (z^2 + (2-2\nu)) [I_1(z)]^2. \quad (3)$$

The initial estimate used for the distance between the zeros along the imaginary axis was π units. Since Newton's method³ worked very well in the similar problem for the hollow cylinder,⁴ it was decided that this method would be used, along with the initial root estimates for the cylinder.

III. THE FAILURE OF NEWTON'S METHOD

Once Newton's method begins to converge, it converges quite rapidly. It is also unfortunately true that once the method begins to diverge, it diverges rapidly. This fact is seen at once from the expression for the error terms.³ We have

$$E_{k+1} = \frac{-f''(\theta)}{2f'(x_k)} (E_k)^2, \quad (4)$$

³R.W. Hamming, *Numerical Methods for Scientists and Engineers*, McGraw-Hill, Inc., New York, 1973.

⁴A.S. Elder, K.P. Zimmerman, "Stresses in a Hollow Elastic Cylinder Produced by a Step Function of Pressure or Shear," Memorandum Report BRL MR 2454, Ballistic Research Laboratory, 1975 (AD A008966).

where E_k is the error in the current estimate x_k of the zero of the function f , E_{k+1} is the error of the next estimate, and θ is some number between x_k and the true zero X . If $f''(\theta)/(2f'(x_k))$ is nearly constant in the vicinity of the root, then the error at each approximation decreases (or increases) as the square of the previous error.

It is therefore critical that the initial estimates of the zeros be quite good when the function has oscillations, as is the case here. In the previously cited case of the hollow cylinder,⁴ at most 9 iterations on Newton's method were required to obtain each of the first five hundred roots, with about 20-digit accuracy. The characteristic equation for the hollow cylinder contains products and cross-products of the four modified Bessel functions I_0 , I_1 , K_0 , K_1 , and evidently the presence of the K function tempers the oscillations somewhat. In addition, a rather good asymptotic approximation to the characteristic function was found, providing excellent initial estimates of the zeros.

Such was not the case for the present work with the solid rod. The initial estimates proved to be insufficiently accurate to provide convergence in Newton's method.

IV. THE MODIFIED METHOD OF BISECTION

It was decided that a root search based on the method of bisection³ might be more fruitful. In simple terms, the method of bisection consists of dividing the region near a zero into a mesh of squares. As a square is traversed in the counterclockwise direction, one evaluates the function, seeking a change in sign of the real and/or imaginary parts. This signifies crossing a zero curve of either the real or the imaginary parts, or both. At this point, the search interval is halved, and the process continues in a direction 90° counterclockwise from the direction just used, until another sign change is encountered.

Because of the analyticity of the function the zeros of which we sought, we did not need to concern ourselves with most of the caveats about the use of bisection techniques. The location of the first several zeros was estimated graphically. This was accomplished by computing functional values in the xy -plane and noting sign changes in the real and imaginary parts. The level

curves $U = 0$, $V = 0$, where $U(x,y) = \text{Re} \{ \Delta(x + 2y) \}$ and $V(x,y) = \text{Im} \{ \Delta(x + 2y) \}$ are shown in Figure 1.

From this point, computation proceeded by estimating the roots to be separated by π units in the direction of the imaginary axis. Although somewhat more cumbersome and time-consuming than Newton's method, the method of bisections provided values of z for which $|\Delta(z)| < 1.0 \times 10^{-20}$ on the BRL CDC 7600 computer. Graphs of the real and imaginary surfaces in the first and fifth quadrants are shown in Figures 2 and 3, respectively. Detail was provided by alternating color contour in these surface plots.

V. CONCLUSIONS

This analysis has shown the method of bisections to be viable tool for use in the method of characteristics. Sensitivity analysis indicated little change beyond the first 10 roots for Poisson's ratio in the range (0.1, 0.5). This information was forwarded along with the tabulation of roots to Prof. Spence.




Figure 1. The Real and Imaginary Parts of $\Delta(z)$ in the xy -Plane




Figure 2. The Real Part of $\Delta(z)$ in the 1st and 5th Quadrants



Figure 3. The Imaginary Part of $\Delta(z)$ in the 1st and 5th Quadrants

REFERENCES

1. K.L. Zimmerman, A.S. Elder, A.K. Depue, "User's Manual for the BRL Subroutine to Calculate Bessel Functions of Integral Order and Complex Argument," Technical Report ARBRI-TR-02068, Ballistic Research Laboratory, 1978 (AD A056369).
2. V.K. Prokopov, "Equilibrium of an Elastic Axisymmetrically loaded Thick-Walled Cylinder," *Prikladnaya matematika i mehanika*, Vol XIII, 1949, pages 135-144. Institute of Mechanics of the Academy of Sciences, USSR, FTIO Translation No. J-2589, Aberdeen Proving Ground, Maryland, Translation dated 22 August 1967.
3. R.W. Hamming, Numerical Methods for Scientists and Engineers, McGraw-Hill, Inc., New York, 1973.
4. A.S. Elder, K.P. Zimmerman, "Stresses in a Hollow Elastic Cylinder Produced by a Step Function of Pressure or Shear," Memorandum Report BRL MR 2454, Ballistic Research Laboratory, 1975 (AD A008966).

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
12	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22314	7	Commander US Army Armament Research and Development Command ATTN: DRDAR-LCR-R, T. Moore DRDAR-LCR, W. Williver DRDAR-LCS-D, K. Reuben DRDAR-LCA S. Bernstein DRDAR-LCN, G. Demitrack DRDAR-LCA, B. Knutulski DRDAR-LCA, T. Davidson Dover, NJ 07801
1	Director Defense Advanced Research Projects Agency 1400 Wilson Boulevard Arlington, VA 22209		
1	Director Defense Nuclear Agency 1801 Beauregard St. Alexandria, VA 22311	2	Commander US Army Armament Research and Development Command ATTN: DRDAR-SE Dover, NJ 07801
1	Commander US Army BMD Advanced Technology Center ATTN: BMDATC-M P.O. Box 1500 Huntsville, AL 35804	1	Commander US Army Armament Research and Development Command ATTN: DRDAR-FU Dover, NJ 07801
1	Commander US Army Materiel Development and Readiness Command ATTN: DRCMDM-ST 5001 Eisenhower Avenue Alexandria, VA 22333	2	Commander US Army Armament Research and Development Command ATTN: DRDAR-DP Dover, NJ 07801
2	Commander US Army Armament Research and Development Command ATTN: DRDAR-TSS Dover, NJ 07801	2	Commander US Army Armament Research and Development Command ATTN: DRDAR-QA Dover, NJ 07801
1	Commander US Army Armament Research and Development Command ATTN: DRDAR-TDC Dover, NJ 07801	2	Commandant US Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905
2	Commander US Army Armament Research and Development Command ATTN: DRDAR-SC, B. Shulman Mr. Webster Dover, NJ 07801	1	Commander US Army Armament Materiel Readiness Command ATTN: DRSAR-LEP-L Rock Island, IL 61299

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Director US Army ARRADCOM Benet Weapons Laboratory ATTN: DRDAR-LCB-TL Watervliet, NY 12189	1	Commander US Army Missile Command ATTN: DRSMI-R Redstone Arsenal, AL 35898
2	Director US Army ARRADCOM Benet Weapons Laboratory ATTN: DRDAR-LCB, T. Simkins Watervliet, NY 12189	1	Commander US Army Missile Command ATTN: DRSMI-YDL Redstone Arsenal, AL 35898
1	Commander US Army Aviation Research and Development Command ATTN: DRDAV-E 4300 Goodfellow Blvd. St. Louis, MO 63120	1	Commander US Army Mobility Equipment Research & Development Command Fort Belvoir, VA 22060
2	Director US Army Research and Technology Laboratories (AVRADCOM) Ames Research Center Moffett Field, CA 94035	2	Commander US Army Tank Automotive Command ATTN: DRSTA-TSL Warren, MI 48090
1	Director US Army Air Mobility Research and Development Laboratory Ames Research Center Moffett Field, CA 94035	2	Project Manager Division Air Defense Gun ATTN: DRCPM-ADG Dover, NJ 07801
1	Commander US Army Communications Research and Development Command ATTN: DRSEL-ATDD Fort Monmouth, NJ 07703	3	Project Manager Cannon Artillery Weapons System ATTN: DRCPM-CAWS Dover, NJ 07801
1	Commander US Army Electronics Research and Development Command Technical Support Activity ATTN: DELSD-L Fort Monmouth, NJ 07703	2	Project Manager Nuclear Munitions ATTN: DRCPM-NUC Dover, NJ 07801
1	Commander US Army Harry Diamond Labs 2800 Powder Mill Road Adelphi, MD 20783	2	Project Manager Tank Main Armament Systems ATTN: DRCPM-TMA Dover, NJ 07801
		1	Product Manager for 30mm Ammo. ATTN: DRCPM-AAH-30mm Dover, NJ 07801
		2	Product Manager M110E2 Weapon System, DARCM ATTN: DRCPM-M110E2 Rock Island, IL 61299

DISTRIBUTION LIST

<u>No. of Copies</u>	<u>Organization</u>	<u>No. of Copies</u>	<u>Organization</u>
3	Commander US Army Research Office P.O. Box 12211 ATTN: Technical Director Engineering Division Metallurgy & Materials Division Research Triangle Park, NC 27709	1	Commander Naval Missile Center Point Mugu, CA 95041
2	Commander US Army Research Office ATTN: Dr. J. Chandra Dr. F. Schmiedeshoff Research Triangle Park NC 27709	1	Commander Naval Surface Weapons Center Dahlgren, VA 22448
4	Director US Army Mechanics and Materials Research Center ATTN: Director (3 cys) DRXMR-ATL (1 cy) Watertown, MA 02172	1	Commander US Naval Surface Weapons Cntr Silver Spring, MD 20910
1	Director US Army TRADOC Systems Analysis Activity ATTN: ATAA-SL White Sands Missile Range NM 88002	1	Commander Naval Weapons Center China Lake, CA 93555
1	Commander Naval Sea Systems Command Navy Department Washington, DC 20362	1	Commander Naval Research Laboratory Washington, DC 20375
1	Commander David W. Taylor Naval Ship Research and Development Center Bethesda, MD 20084	1	Superintendent Naval Postgraduate School ATTN: Dir of Lib Monterey, CA 93940
1	Commander Naval Air Systems Command Washington, DC 20360	1	Commander Naval Ordnance Station Indian Head, MD 20640
1	Commander US Naval Air Development Center, Johnsville Warminster, PA 18974	2	AFRPL ATTN: W. Andrepont T. Park Edwards AFB, CA 93523
		1	AFATL Eglin AFB, FL 32542
		2	AFWL/SUL Kirkland AFB, NM 87115
		1	Director Los Alamos Scientific Lab P.O. Box 1663 Los Alamos, NM 87545
		1	Director Lawrence Livermore Laboratory Livermore, CA 94550

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>	<u>No. of</u> <u>Copies</u>	<u>Organization</u>
1	Headquarters National Aeronautics and Space Administration Washington, DC 20546	1	State University of New York Department of Mathematics ATTN: Dr. Ram Shrivastav Stony Brook, NY 11794
1	Director National Aeronautics and Space Administration Langley Research Center Hampton, VA 23365	2	University of Delaware Department of Mathematics Department of Mechanical Engr. Newark, DE 19711
1	Director National Aeronautics and Space Administration Manned Spacecraft Center ATTN: Lib Houston, TX 77058	1	Princeton University Department of Civil Engineering ATTN: Dr. A.C. Eringen Princeton, NJ 08540
1	AFELM, The Rand Corp. ATTN: Library-D 1700 Main Street Santa Monica, CA 90406	1	University of Kentucky Department of Computer Science ATTN: Prof. H.C. Thacher, Jr. 915 Patterson Office Tower Lexington, KY 40506
1	BLM Applied Mechanics Consultants ATTN: Dr. A. Boresi 3310 Willett Drive Laramie, WY 82070	1	University of Maryland Institute for Physical Science of Technology ATTN: Dr. Frank Olver College Park, MD 20742
1	CALSPAN Corp. ATTN: E. Fisher P.O. Box 400 Buffalo, NY 14225	2	University of Wisconsin-Madison Mathematics Research Center ATTN: Dr. John Nohel Dr. Richard Meyer 610 Walnut Street Madison, WI 53706
1	S&D Dynamics, Inc. ATTN: Dr. M. Soifer 755 New York Avenue Huntington, NY 11743	1	Virginia Commonwealth University 901 W. Franklin Richmond, VA 23284
1	Southwest Research Institute ATTN: P. Cox 8500 Culebra Road San Antonio, TX 78228	1	West Virginia University Dept. of Mech. & Aerospace Eng. ATTN: Prof. G. Inger Morgantown, West Virginia 26506
1	Stanford University Stanford Linear Accelerator Center ATTN: Eric Grosse, Numerical Analysis Consultant ALAC, P.O. Box 4349 Stanford, CA 94305		

DISTRIBUTION LIST

<u>No. of</u> <u>Copies</u>	<u>Organization</u>
<u>Aberdeen Proving Ground</u>	
	Dir, USAMSAA
	ATTN: DRXSY-D
	DRXSY-MP, H. Cohen
	Dir, MTD
	ATTN: H. King
	P. Paules
	Cdr, USATECOM
	ATTN: DRSTE-TO-F
	Dir, USACSL, EA, Bldg E-3516
	ATTN: DRDAR-CLB-PA
	DRDAR-CLN
	DRDAR-CLJ-L

USER EVALUATION OF REPORT

Please take a few minutes to answer the questions below; tear out this sheet, fold as indicated, staple or tape closed, and place in the mail. Your comments will provide us with information for improving future reports.

1. BRL Report Number _____

2. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which report will be used.)

3. How, specifically, is the report being used? (Information source, design data or procedure, management procedure, source of ideas, etc.) _____

4. Has the information in this report led to any quantitative savings as far as man-hours/contract dollars saved, operating costs avoided, efficiencies achieved, etc.? If so, please elaborate.

5. General Comments (Indicate what you think should be changed to make this report and future reports of this type more responsive to your needs, more usable, improve readability, etc.) _____

6. If you would like to be contacted by the personnel who prepared this report to raise specific questions or discuss the topic, please fill in the following information.

Name: _____

Telephone Number: _____

Organization Address: _____

----- FOLD HERE -----

Director
US Army Ballistic Research Laboratory
ATTN: DRDAR-BLA-S
Aberdeen Proving Ground, MD 21005




NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE, \$300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON, DC
POSTAGE WILL BE PAID BY DEPARTMENT OF THE ARMY

Director
US Army Ballistic Research Laboratory
ATTN: DRDAR-BLA-S
Aberdeen Proving Ground, MD 21005



----- FOLD HERE -----